MATERIAL SAFETY DATA SHEET Home Hardware Stores Limited

Page 1 of 4

	Section 1 - Produc	ct and Company Identif	ication
Brand Name:	WEATHER SHIELD		
Item Number:	A125-10		
Material Code:	1823-004, 1823-001		
Chemical Family:	AEROSOL RUST COAT	I GLOSS BLACK	
Intended Use:	AEROSOL-PAINT		
Preparation Date:	27 October 2015		
Prepared By:	AEROSOL LAB	Phone Number:	519-449-2441
Emerger	ncy Phone Number:	(613) 996-6666	
Supplier:		Manufacturer:	
Home Hard	ware Stores Limited	Home Hardware Stores Lim	ited
6 Brian Driv	/e	6 Brian Drive	
Burford, ON	1	Burford, ON	
N0E 1A0		N0E 1A0	

CAS No.	Description	LC50	LD50	LD50	Range
		(ml/m^3)	oral (mg/kg)	Dermal (mg/kg)	
95-63-6	1,2,4-TRIMETHYLBENZENE	36000 (rat)	5000 (rat)	N/AV	0.1% - 1.0%
1333-86-4	CARBON BLACK, AMORPHOUS	N/AP	10000 (rat)	N/AV	0.1% - 1.0%
64742-95-6	NAPHTHA SOLVENT(PETROLEUM), LIGHT AROMATIC	10386 (rat)	8400 (rat)	3480 (rabbit)	1.0% - 5.0%
108-65-6	PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	10644 (rat)	8532 (rat)	5000 (rabbit)	3.0% - 7.0%
75-28-5	ISOBUTANE	285000 (rat)	N/AV	N/AV	5.0% - 10%
8032-32-4	VM&P NAPHTHA	6800 (rat)	5000 (rat)	N/AV	7.0% - 13%
108-88-3	TOLUENE	17600 (rat)	5050 (rat)	12225 (rabbit)	10% - 30%
74-98-6	PROPANE	N/AV	N/AV	N/AV	10% - 30%
67-64-1	ACETONE	34000 (rat)	1750 (rat)	16000 (rabbit)	15% - 40%

Section 3 - Hazards Identification

Emergency Overview: Flammable aerosol. Contents under pressure.

Potential Health Effects

Formula:

A125-10

Routes of Entry: Eye contact, skin contact, skin absorption, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin contact: May cause skin irritation.

Skin contact: Exposure to rapidly expanding gas or vapourizing liquid may cause frostbite (cold burn).

Inhalation: High gas, vapour, mist or dust concentrations may be harmful if inhaled.

Ingestion: May be harmful if swallowed.

Effects of Chronic Exposure to Product: Not available.

Effects Of Acute Exposure: HARMFUL-INHALATION, SKIN & EYE IRRITANT

Section 4 - First Aid Measures

Eye contact: Flush immediately with water for 15 mins. Get medical attention.

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Special training of first aid providers is required. Get medical attention.

Formula: MSDS No.	A125-10 : 1	Home Hardware Stores Limited	Page 2 of 4 13
	Ingestion: Get medical attention im	mediately. Substance may be harmful if swallowed.	
	Skin contact: Wash with soap and w	/ater.	
	S	ection 5 - Fire Fighting Measures	
	Flash Point:	LESS THAN -4C	
	Flash Point Method:	CLOSED CUP	
	Upper Flammable Limit:	13%	
	Lower Flammable Limit:	1%	
	Autoignition:	245 - 530C	
	Hazardous Combustion Products:	OXIDES OF CARBON	
	Means of Extinction:	WATER FOG, DRY CHEMICAL, FOAM	
	Conditions Of Flammability:	FLAMMABLE	
	Explosion Data		
	Mechanical Impact:	NOT SENSITIVE	
	Static Discharge:	VAPOR MAY CATCH FIRE	
	Sect	ion 6 - Accidental Release Measures	
	Absorb spill with inert material. Do	not use combustible materials such as saw dust.	
	Prevent material from entering sewe	ers or confined spaces.	
	Dispose of in accordance with region	nal regulations.	
	5	Section 7 - Handling and Storage	
	Handling Procedures and Equipmer	t: Use only in well vented areas.	
	Handling Procedures and Equipmer	t: Avoid contact with eyes, skin, and clothing.	
	Handling Procedures and Equipmer	t: Avoid breathing vapor, mist, or gas.	
	Storage Requirements: Keep away	from heat, sparks and flame.	
	Storage Requirements: Keep away	from sources of ignition.	
	Storage Requirements: Contents un specified temperature.	der pressure. Do not expose to heat or store above	
	Storage Requirements: Keep away heat. Keep away from food and drin	from sources of ignition. Store away from sources of high k.	
	Section 8	3 - Exposure Control/Personal Protection	
	Specific Engineering Controls: If us minimize exposure.	er operations generate dust, fume, or mist, use ventilation to	
	Specific Engineering Controls: Use	adequate ventilation to reduce airborne vapour levels.	
	Specified Engineering Controls: Go airborne levels.	od general ventilation should be sufficient to control	
	Section	n 9 - Physical and Chemical Properties	
	Appearance:	DPAQUE BLACK LIQUID	
	Odour:	AROMATIC AND KETONE SOLVENT	
	Vapour Pressure:	55-65 PSIG @ 22C	

Vapour Pressure: Vapour Density: Physical State: Boiling Point: OPAQUE BLACK LIQUID AROMATIC AND KETONE SOLVEN 55-65 PSIG @ 22C >1 (AIR = 1) AEROSOL MIXTURE, -42 TO 143C

MATERIAL SAFETY DATA SHEET

Formula: MSDS No.:	A125-10 1	Home Hardware Stores Limited	Page 3 of -
	Freezing/Melting Point:	-95C	
1	pH:	N/AP	
	Evaporation Rate:	FASTER THAN BUTYL ACETATE	
	Coefficient water/oil distr .:	N/AV	
	Odour Threshold:	N/AV	
	Specific Gravity:	0.7432	
		Section 10 - Stability and Reactivity	
	Stability: Yes.		
	Conditions to Avoid: High tem	of ignition, mechanical shock, high temperature.	
	Conditions to Avoid. Sources (Section 11 - Toxicological Information	
	Sensitization to Product: Not av		
		bected human carcinogen-carbon black.	
		fect reproductive system from toluene component (insufficient	
1	evidence).		
		ity from toluene and acetone in animals.	
	Teratogenicity: Maternal toxicit	ty from naphtha solvent (light aromatic petroleum).	
	Mutagenicity: Not available.		
:		gistic Products: Contains ethylbenzene, its break down in the liver is emicals. Also contains xylene which, when combine with solvents ances effects.	
	-	acetone, toluene, xylene and pigments which can cause moderate skin on. Pigment effect is from possible mechanical abrasion.	
		Section 12 - Ecological Information	
-	Not Available.		
		Section 13 - Disposal Considerations	
	Contact your local municipal of	ffice for specific disposal guidelines in your region.	
		Section 14 - Transport Information	
	TDG Road Classification		
	Shipping Name:	AEROSOLS - flammable	
	Class:	2.1	
	Packing Group:	N/AP	
	UN #:	UN1950	
	Limited Quantity Exemption:	1 LITRE	
		Section 15 - Regulatory Information	
	WHMIS Classification:	A, B5, D2A, D2B	
	P.C.P. Registration #:	N/AP	
	EPA Registration #:	N/AP	
	This product has been classified MSDS contains all the informat	I in accordance with the hazard criteria of the CPR and the tion required by the CPR.	
	Canadian National Fire Code 3.	3.5 aerosol storage level 3.	

MATERIAL SAFETY DATA SHEET

Formula: MSDS No.:	A125-10 1	Home Hardware Stores Limited	Page 4 of 4 13
		Section 16 - Other Information	
	N/AV: Not availa	ble	
	N/AP: Not applica	ble	
	NR: Not regulated		
an ha	d was prepared to the be ndling beyond seller's co	al safety data sheet was obtained from sources considered accurate and reliabl st of Home Hardware Stores Limited knowledge. Actual conditions of use and ontrol. User is responsible to evaluate all available information when using use and to comply with all Federal, Provincial and local laws and regulations.	