DURON ^{™/MC} SAE 40

000003000461

Version 2.4

Revision Date 2021/02/24



Print Date 2021/02/24

SECTION 1. IDENTIFICATION

Product name :	DURON TM/MC SAE 40
Product code :	DUR4P20, DUR4DRR, DUR4DRM, DUR4DCT, DUR4C16, DUR4C12, DUR4, DUR4BLK
Manufacturer or supplier's det	Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2 Canada
relephone .	1-905-403-6785
Emergency telephone number	
Emergency telephone num- : ber	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).
Recommended use of the cher	nical and restrictions on use
Recommended use :	DURON single grade oils are intended for use in diesel and spark ignition engines according to the specific viscosity grade and performance level for each grade of product. They may also be used for wet clutch and gear type transmissions and hydraulic systems in line with equipment builder specifica- tions.
Prepared by :	Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high- viscosity; Baseoil — unspecified	72623-85-9	70 - 90

DURON TM/MC SAE 40

000003000461

Version 2.4

Print Date 2021/02/24

72623-87-1	70 - 90
64742-70-7	30 - 50
64742-62-7	10 - 20
113706-15-3	1 - 5
	64742-70-7 64742-62-7

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), sulphur compounds



DURON TM/MC SAE 40

000003000461



(H2S), zinc oxides (ZnOx), metal of smoke and irritating vapours as probustion.	
: Prevent fire extinguishing water from water or the ground water system	5
	smoke and irritating vapours as probustion.Prevent fire extinguishing water fr

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

DURON ^{™/MC} SAE 40

000003000461

Version 2.4

Revision Date 2021/02/24

Print Date 2021/02/24

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil — unspecified	72623-85-9	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-87-1	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
Paraffin oils (petroleum), cata- lytic dewaxed heavy; Baseoil — unspecified	64742-70-7	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
Residual oils (petroleum), sol- vent-dewaxed; Baseoil — un- specified	64742-62-7	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH

Engineering measures

:

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.



DURON TM/MC SAE 40

000003000461

Version 2.4	Revision Date 2021/02/24 Print Date 2021/02					
Personal protective equipment						
Respiratory protection :	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.					
Filter type :	organic vapour filter					
Hand protection						
Material :	neoprene, nitrile, polyvinyl alcohol (F	νVA), Viton(R).				
Remarks :	Chemical-resistant, impervious glove approved standard should be worn a chemical products if a risk assessme essary.	at all times when handling				
Eye protection :	Wear face-shield and protective suit problems.	for abnormal processing				
Skin and body protection :	Choose body protection in relation to tration and amount of dangerous sub cific work-place.					
Protective measures :	Wash contaminated clothing before	re-use.				
Hygiene measures :	Remove and wash contaminated clo ing the inside, before re-use. Wash face, hands and any exposed handling.					

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	amber
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-27 °C (-17 °F)
Boiling point/boiling range	:	No data available
Flash point	:	223 °C (433 °F) Method: Pensky-Martens closed cup
Fire Point	:	274 °C (525 °F)



DURON TM/MC SAE 40

000003000461



0000000000			
Version 2.4		Revision Date 2021/02/24	Print Date 2021/02/24
Evaporation rate	:	No data available	
Flammability	:	Remarks: Low fire hazard. This mater fore ignition will occur.	ial must be heated be-
Auto-Ignition Temperature	:	No data available	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	0.8782 kg/l (15 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	133.2 cSt (40 °C / 104 °F)	
		14.4 cSt (100 °C / 212 °F)	
Explosive properties		Do not pressurise, cut, weld, braze, so pose containers to heat or sources of	

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release COx, SOx, H2S, hydrocarbons, methacrylate monomers, asphyxiants, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of : Eye contact exposure Ingestion Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

DURON

000003000

DURON ^{™/MC} SAE 40			PETRO CANADA
000003000461			
Version 2.4		Revision Date 2021/02/24	Print Date 2021/02/24
		Inhalation Skin contact	
Acute toxicity			
Product:			
Acute oral toxicity	:	Remarks: No data available	
Acute inhalation toxicity	:	Assessment: The substance or mi tion toxicity Remarks: No data available	xture has no acute inhala-
Acute dermal toxicity	:	Assessment: The substance or mi toxicity Remarks: No data available	xture has no acute dermal
<u>Components:</u> Lubricating oils (petroleun Baseoil — unspecified: Acute oral toxicity	n), C: :	2 0-50, hydrotreated neutral oil-ba LD50 (Rat): > 5,000 mg/kg,	sed, high-viscosity;
Acute inhalation toxicity		LC50 (Rat): > 5.2 mg/l	
		Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Lubricating oils (petroleun fied:	n), C	20-50, hydrotreated neutral oil-ba	sed; Baseoil — unspeci-
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l	
		Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Residual oils (petroleum), Acute oral toxicity	solv :	ent-dewaxed; Baseoil — unspecif LD50 (Rat): > 5,000 mg/kg,	lied:
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation			
Product:			

Skin co

Product: Remarks

: No data available

Serious eye damage/eye irritation

Product:

No data available



DURON ^{™/MC} SAE 40

000003000461

Version 2.4



Print Date 2021/02/24

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	Remarks: No data available			
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available			
Toxicity to algae/aquatic plants	:	Remarks: No data available			
Toxicity to microorganisms	:	Remarks: No data available			
Components:					
Residual oils (petroleum), se	olv	ent-dewaxed; Baseoil — unspecified :			
Toxicity to fish	:	EC50 (Fish): > 100 mg/l Exposure time: 96 h			
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h			
Toxicity to algae/aquatic plants	:	EC50 (algae): > 100 mg/l Exposure time: 72 h			
Persistence and degradability					
Product:					
Biodegradability	:	Remarks: No data available			

Bioaccumulative potential

No data available Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

DURON TM/MC SAE 40

000003000461

Version 2.4

Revision Date 2021/02/24



Print Date 2021/02/24

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal
	of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

National Regulations

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this pro		ct are reported in the following inventories: On the inventory, or in compliance with the inventory
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Full text of other abbreviations			
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)	
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)	
CA BC OEL	:	Canada. British Columbia OEL	

DURON ^{™/MC} SAE 40

000003000461



Version 2.4		Revision Date 2021/02/24	Print Date 2021/02/24
CA QC OEL	:	Québec. Regulation respecting occu ty, Schedule 1, Part 1: Permissible e borne contaminants	
ACGIH / TWA	:	8-hour, time-weighted average	
CA AB OEL / TWA	:	8-hour Occupational exposure limit	
CA AB OEL / STEL	:	15-minute occupational exposure lir	nit
CA BC OEL / TWA	:	8-hour time weighted average	
CA QC OEL / TWAEV	:	Time-weighted average exposure va	alue
CA QC OEL / STEV	:	Short-term exposure value	

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); Ecx - Concentration associated with x% response; Elx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2021/02/24 yyyy/mm/dd

DURON ^{™/MC} SAE 40

000003000461

Version 2.4



Revision Date 2021/02/24

Print Date 2021/02/24

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN