

Revised October 20 th , 2017				
	SAFETY DATA SHEET Page 1			
SEC	CTION 1: IDENTIFICATION			
PRODUCT NAME: CIPADITE® E-500 GROUT PART "B				
MANUFACTURER/SUPPLIER:	CPD Construction Products 219 Connie Crescent, Unit #13 Concord, Ontario Canada L4K 1L4			
24 HOUR EMERGENCY NUMBER:	CANUTEC: (613) 996-6666 High strength grout for base plates, anchor bolts, columns etc., where either very high strengths and/or chemical resistance are required.			
PRODUCT DESCRIPTION:	Aggregate filled thermosetting Epoxy Compound. This component is the catalyst only. Cipadite [®] E-500 Grout is a three-component product. There are 3 SDS's for this product.			
SECTION	2: HAZARDS INDENTIFICATION			
GHS CLASSIFICATION:	Acute Toxicity, dermal- 4; Skin corrosion/irritation- 1B; Serious eye damage/ eye irritation- 1; Skin sensitization- 1A; Reproductive Toxicity- 2; Specific target organ toxicity, single exposure- 3 (Respiratory irritation)			
SIGNAL WORD: HAZARD STATEMENTS:	DANGER H312 Harmful in contact with skin H314 Causes severe skin burns and eye damage			
	H317 May cause allergic skin reaction H335 May cause respiratory irritation H361 Suspected of damaging fertility or the unborn child			
PRECAUTIONARY STATEMENTS:				
PREVENTION	P201 Obtain special instruction before use P202 Do not handle until all safety precautions have been read and understood P271 Use only outdoors or in a well-ventilated area P260 Do not breath dust or mist P272 Contaminated work clothing should not be allowed out of the workplace P264 Wash thoroughly after handling P280 Wear protective gloves/ clothing and eye/face protection P308+P311 If exposed or concerned: Call a POISON CENTER or doctor			
	/physician P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse P333+P313 If skin irritation or rash occurs: Get medical advice/ attention P304+P340 IF INHALLED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P301+P330+P331+315 IF SWALLOWED: Rinse mouth. Do not induce vomiting. Get immediate medical advice/ attention			
OTHER HAZARDS:	Ingestion can cause gastrointestinal irritation, nausea and diarrhea. Prolonged inhalation may cause adverse lung effects with symptoms including coughing, mucous production and difficulty breathing.			



		SAFETY	DATA SHEET	Page 2
			NFORMATION ON INGREDIENT	
Hazardous Ingredients	%	C.AS. #	LD/50, Route, Species	LC/50, Route, Species
Triethylenetetramine	40-70	112-24-3	4340 mg/ Kg. (Oral, Rat) 805 mg/ Kg (Dermal, Rabbit)	No Data
Tall Oil Fatty Acids, reaction product with Tetraethylene Pentamine	20-25	68953-36-6	2919-4464 mg/ Kg (Oral, Rat) >2000 mg /Kg (Dermal, Rabbit)	No Data
Tetraethylene Pentamine	3-7	112-57-2	3250mg/ Kg (Oral, Rat) 660-1269 mg/ Kg (Dermal, Rabbit)	No Data
Bisphenol A	1-5	80-05-7	3300 mg/ Kg (Oral, Rat) > 3600 mg/ Kg (Dermal, Rabbit)	> 0.255 mg/L (dust), Inh., Rat
Diethylene Triamine	1-5	111-40-0	1080 mg/ Kg (Oral, Rat) > 0.0 1041 mg/ Kg (Dermal, Rabbit)	07 < 0.3 mg/L (mist), Inh. Rat
Cyclohexanone	1-3	108-94-1	1340 mg /Kg (Oral, Rat) 940 mg/ Kg (Dermal, Rabbit)	2639 ppm (10.6 mg/L) (vapour) Inh. Rat
Tris(dimethylaminomethyl) Phenol	1-3	90-72-2	2169 mg/ Kg (Oral, Rat) 1280 mg/ Kg (Dermal, Rabbit)	No data
		SECTION 4 : FIR	RST-AID MEASURES	
SKIN CONTACTINHALATION		easy to do. Immediatel hair): Remo water/ show Wash conta Immediatel remove per stopped giv qualified m	with water for several minutes. Remove continue rinsing. y call a POISON CENTRE or doctor/physove/ Take off immediately all contaminate wer. If skin irritation or rash occurs: Get minimated clothing before reuse. y call a POISON CENTRE or doctor/ physon to fresh air and keep comfortable for the artificial respiration. If breathing is diffiedical personnel only.	sician. IF ON SKIN (or ed clothing. Rinse skin with dedical advice/attention. rsician. IF INHALLED: breathing. If breathing has deult give oxygen by
INGESTION			y call a POISON CENTRE or doctor/ phy h. DO NOT induce vomiting. Never give s person.	
SYMPTOMS AND EFFECTS,		DELAYED		
SKIN CONTACTSKIN CONTACT		Harmful in tissues. Cau burns, deep skin reactio	ere eye damage. contact with skin. May be absorbed throu uses severe skin burns. Direct skin contact ulcerations and possibly permanent scarr on (e.g. swelling, rash and eczema) Allergi ours after exposure.	may cause corrosive skin ing. May cause an allergic
INHALATION		Harmful if cause sever include cou	inhaled. May cause respiratory irritation. It is irritation to the nose, throat and respirate ghing, chest pain and shortness of breath.	ory tract. Symptoms may
NOTE TO THE PHYSICIAN .		digestive tra cramping a	an cause irritation and corrosive action in act. Symptoms include: Gastrointestinal d and diarrhea. Suspected of damaging fertilit of accidental exposure immediate medicatedly.	iscomfort, nausea, vomiting, ity or the unborn child.



	SAFETY DATA SHEET Page 3			
SECTION	N 5: FIRE-FIGHTING MEASURES			
SUITABLE EXTINGUISHING MEDIA	Carbon dioxide (CO ₂), dry chemical or alcohol foam. Do not use a solid water stream as it may scatter and spread fire. Closed containers may rupture if exposed to excess heat or flame due to a build-			
FLAMMABILITY CLASSIFICATION	up of internal pressure. Not flammable, according to OSHA 29 CFR 1910.106. Carbon oxides. Nitrogen oxides, Hydrogen cyanide, Ammonia, Amines, Aldehydes, Ketones and other irritating fumes and smoke.			
FIRE-FIGHTERS PROTECTIVE EQUIPMENT	Fire-fighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces, fire-fighters should wear an approved full face, self-contained breathing apparatus (SCBA) and impervious clothing.			
SPECIAL FIRE FIGHTING PROCEDURES	Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Do not allow run-off from the firefighting to enter drains or water courses. Dike for water control.			
SECTION 6:	ACCIDENTAL RELEASE MEASURES			
PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY				
PROCEDURES	Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.			
ENVIRONMENTAL PRECAUTIONS	Ensure spilled product does not enter drains, sewers, waterways or confined spaces. For large spills, dike the area to prevent spreading.			
METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN-UP	Ventilate the area. Remove all sources of ignition. Stop the spill at source if it is safe to do so. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand). Pick up and transfer to properly labelled containers. Refer to Section 13 for disposal of contaminated material. Contact the proper local authorities.			
SPECIAL SPILL RESPONSE PROCEDURES	If a spill/ release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response centre in the United States (phone: 1-800-424-8802) or the appropriate local authorities.			
SECTION 7: HANDLING AND STORAGE				
PRECAUTIONS FOR SAFE HANDLING	Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Persons with recurring skin eczema or sensitization problems should be excluded from working with this product. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted. Wear protective gloves/ clothing and eye/ face protection. Contaminated work clothing must not be allowed out of the workplace. Do not breath dust or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Wash thoroughly after handling. Keep containers tightly closed when not in use. Keep away from extreme heat and flame. Take precautions to prevent premature mixing of components and subsequent premature curing.			
CONDITIONS FOR SAFE STORAGE	Store locked up. Keep containers tightly closed. Store in a well-ventilated place. Store away from incompatible materials. Inspect periodically for damage or leaks. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. No smoking in the area.			



	SAFETY DATA S	HEET		Page 4
SECTION 8: EXPOS	URE CONTROLS /	PERSONAL	PROTECTION	
EXPOSURE LIMITS:	ACGIH '	TLV	OSHA PEL	4
	TWA	STEL	PEL PEL	STEL
TRIETHYLENETETRAMINE	1 ppm (skin) (AIHA WEEL)	N/Av	N/Av	N/Av
TETRAETHYLENEPENTAMINE	5 mg/ m³ (skin) (AIHA WEEL)	N/Av	N/Av	N/Av
DIETHYLENETRIAMINE	1 ppm (skin)	N/Av	1 ppm (final rule limit)	N/Av
CYCLOHEXANONE	20 ppm (skin)	N/Av	$50~ppm~(200~mg/~m^3)$	N/Av
EXPOSURE CONTROLS: VENTILATION/ ENGINEERING MEASURES:	occupational exposu	re limits. Where	ply technical measures to com reasonably practicable this sh- ventilation and good general e	ould be
RESPIRATORY PROTECTION	If airborne concentra known, use NIOSH- on the form and conc OSHA (29CFR 1910 cartridge respirators	tions are above approved respiration of condition of CSA Zare recommender	the permissible exposure limit ators. Respirators should be selutaminants in air, and in accord 194.4-02. NIOSH approved orged. Advice should be sought from the sought from t	or are not lected based lance with ganic vapour
SKIN PROTECTION	respiratory protection specialists. Wear protective gloves/ clothing. Gloves impervious to the material are recommended. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.			
EYE/ FACE PROTECTION	Wear eye/ face protection. Chemical splash goggles are recommended. A full face shield may also be necessary.			
OTHER PROTECTIVE EQUIPMENT	An eyewash station and safety shower should be made available in the immediate working area. Other equipment may be required depending on workplace standards.			
GENERAL HYGIENE CONSIDERATIONS	Do not eat, drink, sm not breath dust or mis creams may help to p applied once exposur before eating, drinkir	st. Avoid contact rotect the expose has occurred. Ig, smoking or ug before re-use.	netics while working with this part with eyes, skin and clothing. Seed areas of skin; they should have Upon completion of work, was use of toilet facilities. Remove Contaminated clothing must not be the contaminated clothing must not be contaminated clothing must not be contaminated clothing must	Barrier nowever not be sh hands and wash
SECTION 9: PH	IYSICAL AND CHE	EMICAL PRO	PERTIES	
APPEARANCE	Clear amber liquid			
ODOUR	Amine Odour			
ODOUR THRESHOLD	Not available			
pH LEVEL	Not available			
MELTING/ FREEZING POINT	Not available			
BOILING POINT	250°C (482°F)			
FLASH POINT	Not available			
EVAPORATION RATE	Not available			
FLAMMABILITY	Not applicable			
VAPOUR PRESSURE	Less than 1 mmHg @ 20°C (68°F)			
VAPOUR DENSITY (Air=1) (mg/m3)	5.04			
SPECIFIC GRAVITY @ 20°C (68°F)	0.980			
VISCOSITY	100 cps @ 20°C (68°	F)		
VOLATILES (% by WEIGHT)	Not available			
VOC's (Volatile Organic Compounds)	0 grams/L			
SOLUBILITY IN WATER (%W/W)	Partially soluble			



SAFETY DATA SHEET Page 5				
SECTION 10: STABILITY AND REACTIVITY				
REACTIVITY	Not normally reactive.			
CHEMICAL STABILITY	Stable under the recommended storage and handling conditions prescribed.			
HAZARDOUS REACTIONS	Hazardous polymerization does not occur.			
CONDITIONS TO AVOID	Avoid heat and open flame. Avoid contact with incompatible materials. Ensure			
	adequate ventilation, especially in confined areas.			
INCOMPATIBLE MATERIALS	Acids. Oxidizing agents. Acid chlorides. Acid anhydrides. Aldehydes. Ketones.			
	Acrylates.			
HAZARDOUS DECOMPOSITION PRODUCTS				
SECTION 11	: TOXICOLOGICAL INFORMATION			
LIKELY ROUTES OF EXPOSURE	Inhalation, skin and eye contact, ingestion, skin absorption.			
SIGNS AND SYMPTOMS OF EXPOSURE				
INHALATION	May cause respiratory irritation. If mists are formed, may cause severe irritation			
	to the nose, throat and respiratory tract. Symptoms may include coughing, chest			
	pain and shortness of breath.			
INGESTION	Ingestion can cause irritation and corrosive action in the mouth, stomach and			
	digestive tract. Symptoms include: Gastrointestinal discomfort, nausea,			
	vomiting, cramping and diarrhea.			
SKIN CONTACT	Harmful in contact with skin. May be absorbed through the skin. Corrosive to all			
	tissues. Causes severe skin burns. Direct skin contact may cause corrosive skin			
	burns, deep ulcerations and possibly permanent scarring.			
EYE CONTACT	Corrosive to eyes. Causes serious eye damage. Direct eye contact may produce			
	severe irritation with possible eye damage.			
CHRONIC HEALTH EFFECTS	Prolonged inhalation may cause adverse lung effects with symptoms including			
	coughing, mucous production and difficulty breathing.			
MUTAGENICITY	Not expected to be mutagenic in humans.			
CARCINOGENICITY	No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP			
REPRODUCTIVE EFFECTS	This material is classified as hazardous under U.S. OSHA regulations (29			
	CFR1910.1200) (Hazcom2012) and Canadian WHMIS regulations (Hazardous			
	Products Regulations) (WHMIS 2015) Classification: Reproductive Toxicity-			
	Category 2 Suspected of damaging fertility or the unborn child.			
SENSITIZATION TO MATERIAL	This material is classified as hazardous under U.S. OSHA regulations (29			
SENSITIZATION TO WANTERINE	CFR1910.1200) (Hazcom2012) and Canadian WHMIS regulations (Hazardous			
	Products Regulations) (WHMIS 2015) Classification: Skin sensitization-			
	Category 1A- May cause allergic skin reaction.			
	Not expected to be a respiratory sensitizer.			
SPECIFIC TARGET ORGAN EFFECTS	Eyes, skin, respiratory system and digestive system.			
SPECIFIC TARGET ORGAN EFFECTS	This material is classified as hazardous under U.S. OSHA regulations (29			
	CFR1910.1200) (Hazcom2012) and Canadian WHMIS regulations (Hazardous			
	Products Regulations) (WHMIS 2015) Classification: Specific target organ			
	toxicity, single exposure- Category 3 May cause respiratory irritation.			
MEDICAL CONDITIONS AGGRAVATED	Not classified as specific target organ toxicity- repeated exposure.			
BY OVEREXPOSURE	Dra avieting ekin ava and recoiretary disorders			
SYNERGISTIC MATERIALS	Pre-existing skin, eye, and respiratory disorders. Not available.			
TOXICOLOGICAL DATA	There is no data available for this product.			
INGREDIENTS LD50/ LC50 DATA	Refer to Section 3.			
	12: ECOLOGICAL INFORMATION			
ECOTOXICITY	Not expected to be harmful to aquatic organisms. However, this does not exclude			
	the possibility that large or frequent spills can have a harmful or damaging effect			
	on the environment. Avoid release to the environment.			
PERSISTANCE AND DEGRADABILITY	No data is available on the product itself.			
BIOACCUMULATION POTENTIAL	No data is available on the product itself.			
MOBILITY IN SOIL	No data is available on the product itself.			



	SAFETY DATA SHEET	Page 6
SECTION	13: DISPOSAL CONSIDERATIONS	
HANDLING FOR DISPOSAL	Handle in accordance with good industrial hygiene and safety emptied containers may retain product residue, follow label value container is emptied. Refer to protective measures listed in S	warnings even after
METHODS OF DISPOSAL	Dispose in accordance with all federal, state, provincial and l	ocal regulations.
RCRA	If this product, as supplied, becomes a waste in the United St the criteria of a hazardous waste as defined under RCRA, Tit the responsibility of the waste generator to determine the pro-	le 40 CFR 261. It is
OT CONTON A	identification and disposal method.	
SECTION 14	: TRANSPORTATION INFORMATION	
IN ACCORDANCE WITH ALL TDG; 49CFR/DOT; ICAO/ IATA; IMDG CRITERIA:	Corrosive liquid, Basic, Organic, N.O.S. (Triethylenetetramic Tetraethylene Pentamine) UN3267, Class 8, PG II	ne,
	8	
SPECIAL PRECAUTIONS FOR USERS ENVIRONMENTAL HAZARDS	Appropriate advice on safety must accompany the package This product does not meet the criteria for an environmental according to the IMDG Code. Refer to Section12.	hazardous mixture,
TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE		
IBC CODE	This information is not available.	
SECTION	15: REGULATORY INFORMATION	
CEPA INFORMATION	All ingredients listed appear on the Domestic Substances Lis	t (DSL)
WHMIS CLASSIFICATION	Class D, Division 2, Subdivision B Class E, Corrosive	
CPR (CANADA) COMPLIANCE	Meets all requirements.	
SECTI	ON 16: OTHER INFORMATION	
ACGIH	American Confederation of Governmental Industrial Hygien	ists
IARC	International Agency for Research on Cancer	
NTP	National Toxicology Program	
STEL	Short Term Exposure Limit	
PEL	Permissible Exposure Limit	
TLV-TWA	Threshold Limit Value - Time-Weighted Average	
OSHA	Occupational Safety and Health Administration	
NIOSH	National Institute for Occupational Safety and Health	
RCRA	Resource Conservation and Recovery Act	
CPR	Controlled Products Regulations	
CEPA	Canadian Environmental Protection Act	
CERCLA	Comprehensive Environmental Response, Compensation and	l Liability Act
CAS	Chemical Abstracts Service	
PPE	Personal Protection Equipment	
N/Av	Not available	
PREPARED BY:	Camelia Gardo	
PREPARED BY: TELEPHONE NUMBER:	Camelia Gardo (905) 669-5013	

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.